

Секция N3. Смешение + фильтрация EU4 + водяной нагрев





N3

Рядность теплообменника нагревателя

2

Смешение + фильтрация EU4 + водяной нагрев



Типо-раз-мер	A, мм	B, мм	B, мм		Г, мм	Д, мм	Резьбовое соединение	
			2-рядное исполнение	3-рядное исполнение			2-рядное исполнение	3-рядное исполнение
6	1100	1100	735	722	85	1625	G1 ¹ / ₄ "	G1 ¹ / ₂ "
7	1100	1320	985	972	85	1625	G1 ¹ / ₂ "	G1 ¹ / ₂ "
8	1320	1320	985	985	85	1625	G1 ¹ / ₂ "	G2"
6.1	1435	770	518	501	85	1275	G1 ¹ / ₂ "	G1 ¹ / ₂ "
7.1	1597	850	590	592	85	1275	G1 ¹ / ₂ "	G1 ¹ / ₂ "
8.1	1706	905	667	647	85	1275	G1 ¹ / ₂ "	G1 ¹ / ₂ "
10	1877	990	707	710	85	1275	G1 ¹ / ₂ "	G1 ¹ / ₂ "
12	1435	1435	1060	1152	85	2150	G2"	G2"
18	2095	1100	812	810	85	1275	G1 ¹ / ₂ "	G2"
20	1660	1660	1355	1355	85	2150	G2"	G2 ¹ / ₂ "
21	2320	1212	905	912	85	1275	G2"	G2"
23	2536	1320	1010	1007	85	1275	G2"	G2 ¹ / ₂ "
24	2764	1435	1106	1106	85	1275	G2 ¹ / ₂ "	G2 ¹ / ₂ "
25	2045	2045	1740	1740	85	2150	G2 ¹ / ₂ "	G3"
30	2485	2045	1685	1685	100	2150	G2 ¹ / ₂ "	G3"
31	3180	1660	1350	1350	182	1975	G3"	G3"
35	2485	2485	2125	2100	125	2150	G3"	G4"
36	3650	1877	1560	1560	182	1975	G3"	G3"